

## LATHE OPTIMUM Ø560 X 2.000 MM

**Manufacturer:** Optimum  
**Type:** TU 5620V  
**Year:** 2014  
**Price:** on request



### Turning lathe Optimum

Distance between centres: 2.000 mm  
Turning diameter: 560 mm over bed  
355 mm over cross slide

Digital readout: 2 Axis (X/Y)  
Spindle speed: 0 - 1.600 rpm  
Spindle bore: 58 mm

Feed on X-axis: 0,059 ~ 1,646 mm/rev.  
Feed on Y-axis: 0,020 ~ 0,573 mm/rev.

Featured with:

- 3 + 4-Jaw Chuck
- 1x Following steady
- 1x Fixed steady
- Toolcutter holders
- Various tooling
- Cooling unit
- User manuals

Country of origin: Germany  
Motor power: 7,5 kW  
Machine weight: 3.100 kg

---

## TECHNICAL SPECIFICATIONS

<b>Turning lathe Optimum:</b>	
<b>Distance between centres:</b>	2.000 mm
<b>Turning diameter:</b>	560 mm over bed 355 mm over cross slide
<b>Digital readout:</b>	2 Axis (X/Y)
<b>Spindle speed:</b>	0 - 1.600 rpm
<b>Spindle bore:</b>	58 mm
<b>Feed on X-axis:</b>	0,059 ~ 1,646 mm/rev.
<b>Feed on Y-axis:</b>	0,020 ~ 0,573 mm/rev.
<b>Featured with:</b>	<ul style="list-style-type: none"><li>- 3 + 4-Jaw Chuck</li><li>- 1x Following steady</li><li>- 1x Fixed steady</li><li>- Toolcutter holders</li><li>- Various tooling</li><li>- Cooling unit</li><li>- User manuals</li></ul>
<b>Country of origin:</b>	Germany
<b>Motor power:</b>	7,5 kW
<b>Machine weight:</b>	3.100 kg