

## PORTALMILLINGMACHINE OKUMA X: 3000MM

**Manufacturer:** Okuma  
**Type:** MCV 20A II  
**Year:** -  
**Price:** on request



## TECHNICAL SPECIFICATIONS

|                                  |  |
|----------------------------------|--|
| <b>X-axis:</b>                   | 3.000 mm   |
| <b>Y-axis:</b>                   | 2.000 mm   |
| <b>Z-axis:</b>                   | 1.150 mm   |
| <b>Table size:</b>               | 2.800 x 1.500 mm   |
| <b>Spindle nose:</b>             | ISO 50   |
| <b>Spindle speeds:</b>           | 30 - 6.000 rpm   |
| <b>ATC:</b>                      | 50 pockets   |
| <b>CNC controller:</b>           | OSP7000M   |
| <b>Distance between columns:</b> | 2.050 mm   |
| <b>Featured with:</b>            | <ul style="list-style-type: none"><li>- Vertical milling head attachment</li><li>- Touch probe</li><li>- Double chip conveyor (recently renewed)</li><li>- Cooling unit (recently renewed)</li><li>- Machine manuals</li></ul> |
| <b>Country of origin:</b>        | Japan  |
| <b>Machine LxWxH:</b>            | 9.000 x 3.500 x 3.500 mm +/-   |
| <b>Machine weight:</b>           | 27.500 kg  |